



Varzseal® AC1102

Water-based acrylic paint
Semi-gloss paint for interior surfaces of building

INTRODUCTION

Type of paint:

Water-based, made with acrylic resin

Usage:

Varzseal® can be used to paint gypsum, cement, concrete, stone, brick and wood interior surfaces. It is also suitable for use on residential areas and crowded areas such as hospitals, schools, universities, transportation terminals and parking walls.

Properties:

One of the advantages of Varzseal® paint is excellent coverage. It is odorless, possesses good adhesion to internal surfaces, fast drying, good washing ability, easy and fast application, free of lead and other harmful agents.

APPLICATION AND STORAGE

Surface preparation:

Clean the surface from any contamination. If necessary, calk the surface with primer and after polishing, completely remove dust from the surface and then start painting.

Application procedure:

After opening the cap of the container, stir the paint thoroughly before use. It is recommended to mix the paint with 20-30% of clean water in two stages.

Application equipment:

Brush, roller or airless spray

Airless spray application:

Pressure: 150 to 180 bar

Tip angle: 50°

Tip size: 0.021" to 0.026"





Varzseal® AC1102

Storage condition:

Keep in dry and cool environment and away from direct sunlight at a temperature of +5 to +45 degrees Celsius. It is best to use paint within one year after the production date.

TECHNICAL INFORMATION

Theoretical Coverage	10 to 12 m ² /Liter
Appearance	Viscous liquid
Color	White
Specific gravity	1.5 ± 0.2 gr/cm ³
Solid content	65%
Surface drying time	Max. 2 hrs.
Next layer application time	Min. 3 hrs.

It should be noted that drying time of the applied paint depends on air flow, air temperature, humidity, thickness and the number of layers.

